

# PORTABLE PHLEGM SUCTION UNIT

**Model: H003-B**



## Main Technical Specifications

1. Ultimate negative pressure value:  $\geq 0.075\text{MPa}$
2. Regulating scope of negative pressure:  $0.02\text{MPa} \sim$  ultimate negative pressure value
3. Air exhausting speed:  $\geq 11\text{L/min}$
4. Reservoir:  $\geq 1000\text{ mL}$ , 1pc
5. Power supply: AC220V/110V and 50/60Hz,
6. Input power: 90VA
7. Noise:  $\leq 65\text{dB(A)}$
8. Suction pump: piston pump
9. Dimension: H003-B:  $19.6 \times 23.5 \times 24.3\text{ (cm)}$

- Electric classification: application part of class II type B
- Operation mode: short-time operation
- The suction unit is not suitable to use on occasions with inflammable and explosive gas.
- Class of liquid-proof: IPX0
- Non AP or APG device
- No signal input or signal output

## Normal Working Condition

Ambient temperature:  $5^{\circ}\text{C} - 40^{\circ}\text{C}$

Relative humidity:  $\leq 80\%$

Atmospheric pressure:  $86\text{kPa} - 106\text{kPa}$

- When storage and transportation temperature is lower than  $5^{\circ}\text{C}$ , the suction unit shall be placed in the place with normal working temperature for over 4 hours before use.
- To avoid potential electromagnetic interference existing between the equipment and other devices, the suction unit is suggested to be kept away from high frequency equipment.

## List of Accessories

Fuse (F1.5AL 250V $\phi 5 \times 20$ )	2 pieces
Silicone hose	3 pieces
Air filter	3 pieces
Disposable suction head	2 pieces
Catheter package	2 pieces

