

PORTABLE PHLEGM SUCTION UNIT

Model: H003-C



Main Technical Specifications

1. Ultimate negative pressure value: $\geq 0.075\text{MPa}$
 2. Regulating scope of negative pressure: $0.02\text{MPa} \sim$ ultimate negative pressure value
 3. Air exhausting speed: $\geq 18\text{L/min}$
 4. Reservoir: $\geq 1000\text{ mL}$, 1pc
 5. Power supply: AC220V/110V and 50/60Hz
 6. Input power: 90VA
 7. Noise: $\leq 65\text{dB(A)}$
 8. Suction pump: piston pump
 9. Dimension: 335mm X 150mm X 240mm
- Electric classification: application part of class II type B
 - Operation mode: short-time operation
 - The suction unit is not suitable to use on occasions with inflammable and explosive gas.
 - Class of liquid-proof: IPX0

Normal Working Condition

Ambient temperature: $5^{\circ}\text{C} - 40^{\circ}\text{C}$

Relative humidity: $\leq 80\%$

Atmospheric pressure: 86kPa-106kPa

- When storage and transportation temperature is lower than 5°C , the suction unit shall be placed in the place with normal working temperature for over 4 hours before use.
- To avoid potential electromagnetic interference existing between the equipment and other devices, the suction unit is suggested to be kept away from high frequency equipment.

List of Accessories

Fuse (F1.5VL250V, $\phi 5 \times 20$)	2 pieces
Silicone hose	3 pieces
Air filter	3 pieces
Disposable suction head	2 pieces
Catheter package	2 pieces

